

ENGINE OPTION MODEL
Motorausführung

1B20 -7

(Zy1.)




ENGINE OPTION MODEL
Motorausführung

1B20 -9


(Zy1.)

SAE A

($\emptyset 41.25^{+0.025}$)





DETAIL "Z"




SAE A


($\emptyset 41.25^{+0.025}$)




D. STRAIGHT



DETAIL "Y"



D : SCREWS WITH SEALANT
(FOR EXAMPLE LOCTITE 221)
D : Schrauben mit Dichtmittel
(z.B. Loctite 221)



Dimensiones without tolerance indication are nominal size.

Maße ohne Toleranzangaben sind Nennmaße

In the interests of technical progress we reserve the right to introduce modifications.
Änderungen, die dem technischen Fortschritt dienen, behalten wir uns vor.

The range of the length over-all based on tolerances can add up to ± 3 mm
Toleranzbedingte Streubreite bei Kastenmassen ± 3 mm

PROTECTION MARK
ACC. TO DIN 34

Schutzvermerk nach
DIN 34 beachten

HATZ

MOTORENFABRIK
HATZ

RUHSTORF-ROTT

INSTALLATION DRAWING
Einbauzeichnung

1B20

SHAFTS AT GOVERNOR-SIDE
Wellen auf sts.

SHEET OF SHEETS
Blatt 10 von 11 Blättern

gez.: 03.11.08 Gerh gepr.: 03.11.08 Mad1